



波形弹簧式机械密封
Component seal series (Wave spring type seals)

1	2	3	4	5	6	7	8				
Size/Metric	d	D3	D6	D7	D8	L3	L4	L5	F	M	
A	18	18	32	27	33	3	30.5	7.0	15.0	3.0	M4
	20	20	34	29	35	3	30.5	7.0	15.0	3.0	M4
	22	22	36	31	37	3	30.5	7.0	15.0	3.0	M4
	24	24	38	33	39	3	33.0	7.0	15.0	3.5	M5
	25	25	39	34	40	3	33.0	7.0	15.0	3.5	M5
	28	28	42	37	43	3	35.5	7.0	15.0	3.5	M5
	30	30	44	39	45	3	35.5	7.0	15.0	3.5	M5
	32	32	47	42	48	3	35.5	7.0	15.0	3.5	M5
B	33	33	47	42	48	3	35.5	7.0	15.0	3.5	M5
	35	35	49	44	50	3	35.5	7.0	15.0	3.5	M5
	38	38	54	49	56	4	37.0	8.0	16.0	4.0	M5
	40	40	56	51	58	4	37.0	8.0	16.0	4.0	M5
	43	43	59	54	61	4	37.0	8.0	16.0	4.0	M5
	45	45	61	56	63	4	37.0	8.0	16.0	4.0	M5
C	48	48	64	59	66	4	37.0	8.0	16.0	4.0	M5
	50	50	66	62	70	4	38.0	9.5	17.0	4.5	M6
	53	53	69	65	73	4	38.0	9.5	17.0	4.5	M6
	55	55	71	67	75	4	38.0	9.5	17.0	4.5	M6
	58	58	78	70	78	4	42.0	10.5	18.0	4.5	M6
	60	60	80	72	80	4	42.0	10.5	18.0	4.5	M6
D	63	63	83	75	83	4	42.0	10.5	18.0	4.5	M6
	65	65	85	77	85	4	42.0	10.5	18.0	4.5	M6
	68	68	88	81	90	4	41.5	11.0	18.5	4.5	M6
	70	70	90	83	92	4	48.5	11.5	19.0	5.0	M8
	75	75	99	88	97	4	48.5	11.5	19.0	5.5	M8
	80	80	104	95	105	4	48.5	11.5	19.0	5.5	M8
E	85	85	109	100	110	4	48.5	11.5	19.0	5.5	M8
	90	90	114	105	115	4	52.0	13.0	20.5	5.5	M8
	95	95	119	110	120	4	52.0	13.0	20.5	5.5	M8
F	100	100	124	115	125	4	52.0	13.0	20.5	5.5	M8

结构说明(Structure Description):
Equivalent to AES M010, Burgmann HJ92N
波形弹簧密封, 平衡型密封 (Wave spring design - balanced seal)

运行参数(Operating Limits):
温度(Temperature): -20---180°C
线速(Speed): 15m/s
压力(Pressure): 25bar
标准尺寸(Standard size): 18 - 100mm

常用材料组合(Material):
密封唇(Seal ring): 石墨, 碳化硅, 氧化铝 (Car, Sic, Sic, TC)
辅助密封(Secundary seals): 丁腈橡胶, 氟橡胶等 (NBR, EPDM, Viton etc)
金属弹簧(Spring and metal parts): 304, 316, HAST.C

CUSTOMER:	www.asinoseal.com	ASINOSEAL CO.,LTD 张家港爱斯派机械密封有限公司
P.O. NO.:	Tel:+86-512-58227959 Fax:+86-512-58228759	
REF:	Mail:sales@asinoseal.com	Installation Drawing
DRAWN BY:	No.265 South Chang'An Rd,Zhangjiagang ,China	
CHECKED:		TYPE & SIZE:
APPVD:		AS-R92N
SCALE:	DATE:	PAGE:X/X

